

# DATA SHEET PRIMER QUARZ

It is a water based resin, with excellent adhesion on any surface with little or no porosity, and a permanent residual tack that ensures adhesion between coats. It has a high elasticity, maintaining this property for long high resistance to water and alkalis and therefore excellent resistance to different atmospheric conditions. Excellent resistance to different atmospheric conditions.

## RECOMMENDED USES

- Bonding bridge between finishes and surfaces with little porosity.
- Bonding bridge between tiles, stoneware and mortars.
- Bonding bridge between old walls and new applications
- Increasing the bond between old walls and new applications.
- Filling of small cracks to absorb building expansions.
- Fixing of earthy and crumbly surfaces
- Waterproofing of facades

## TECHNICAL CHARACTERISTICS

**Appearance:** White liquid

**Density:** 1± .04 gr /cm<sup>3</sup>

**Application temperature:** +0 °C to +30 °C

**Toxicity / Flammability:** No

## APPLICATION

For applications on smooth, slightly porous finishes, it should be used undiluted.

For porous surfaces it can be diluted 20%-30% with water and applied in several coats.

## PERFORMANCE

Depends on the absorption of the substrate.

## RECOMMENDATIONS TO BE TAKEN INTO ACCOUNT DURING THE APPLICATION PROCESS

It is essential to use protective glasses and gloves during the application and mixing process.

mixing process. If the product comes into contact with the eyes, wash them immediately with plenty of water. immediately with plenty of water and seek medical attention.

## CLEANING

Tools should be cleaned with water within 30 minutes of use. Afterwards, mechanical means should be used.

## PRESENTATION

PrimerQuarz is available in 1kg and 5kg containers.

## STORAGE

At least 12 months in original containers in a dry and protected environment.