

# DATA SHEET PRIMER FINISH

One-component primer in aqueous acrylic-polyurethane aliphatic polyether-based dispersion. Easy and quick to apply by roller or brush. Very good anchorage on different types of substrates (concrete floors, microcement, etc.). Suitable as a transparent sealing primer for outdoor use, does not yellow due to UV rays. Not recommended as a final finish.

## TECHNICAL SPECIFICATIONS

### PRODUCT SPECIFICATION

**Density:** 1,00 - 1,05 gr./cc.

**Colour:** Transparent

**Appearance:** Opalescent liquid

**Solid content:** 22,5% by weight

### CHARACTERISTICS OF THE DRY PRIMER

**Appearance:** Glossy Tack-Free (non-sticky)

**Colour:** Colourless

## APPLICATION

Brush or roller.

## SUBSTRATE

All materials normally used in construction, clean and dry. Not suitable for non-porous substrates.

## DILUTION

Ready-to-use product, no dilution required.

## DRYING

Recoating 1-3hs depending on the temperature and relative humidity of the environment and the absorption of the substrate.

## APPLICATION CONDITIONS

Apply at room and substrate temperatures between +10 and 30 °C. Do not apply with relative humidity higher than 70%. The substrate temperature should be at least 3 °C above the dew point.

## WARNINGS

- Do not use the product at -5°C and +30°C.
- Stir the product with an electric stirrer before use.
- Do not leave the containers open for a long time.
- Do not use products that intervene in the system if they are not recommended by Ecoresinas.
- Do not add water or additives to the product.
- Do not accelerate the drying process with heaters during the days after application until curing.

## CLEANING

The tools should be cleaned with water within 120 minutes of use, mechanical means should be used thereafter.

## **PRESENTATION**

Primer Finish is available in 1kg and 5kg packs.

## **STORAGE**

Containers should be stored in cool, dry rooms for a maximum of 12 months.

The product should be kept in its original sealed container, keeping the manufacturer's reference, product name, batch number and safety labels.

C/Reina Elionor 25-27 • 08205 Sabadell (Barcelona)

T. (+34) 977 079 111 • [info@ecoresinas.com](mailto:info@ecoresinas.com)

**ecoresinas.com**